



PRODUCT LINEUP

# AIR TO WATER

For RESIDENTIAL

Room Heating & Cooling

Domestic Hot Water

Swimming Pool

## Complete Solution meets various needs

The clean energy produced by WATERSTAGE™ reliably delivers "comfort" to all spaces in the home up to the living room, bedrooms, bath, and swimming pool.


# WATERSTAGE™



- 240 SOLUTIONS
- 242 CORE TECHNOLOGY
- 243 WATERSTAGE™ Lineup
- 244 Split Type
  - Split DHW Integrated Type
- 246 Monobloc Type
- 247 Case Studies
- 248 Optional Parts
- 250 Installation Limitations
- Specifications & Dimensions

## What's a Heat Pump ?

Absorbing free energy from the atmosphere. Heat pump system requires only 1 kW of electricity to generate 3 to 5 kW thermal energy.








# HOME HEATING


Wide range lineup suited for regional characteristics, family structure, and application. We provide various products to meet your needs from High Power via heating-centered series to reasonably-priced compact series

## WATERSTAGE™





## High leaving water temperature

High leaving water temperature 60°C kept down to -20°C outdoor temperature without using backup heater.



## Smart control

User's needs are supported by offering a variety of controls, such as individual control and remote control options.



## + DHW Tank

DHW tank (option) can be used to supply hot water by connecting it to the system.

## + Boiler

By combining existing boiler, powerful heating can be performed even at low outdoor temperature.

Stylish space saving solution with built-in DHW tank



## Space is saved drastically due to built-in DHW tank.

Existing boiler can be replaced easily. A larger heating capacity can be performed flexibly by using more units in cascade connection.




NEW

## For Room heating & domestic hot water

### Split type Super High Power series

Outdoor unit and hydraulic indoor unit can be installed freely, so installation is easy. Since hydraulic indoor unit is installed inside a house, freezing of circulated water can be prevented. A larger heating capacity can be performed flexibly by using more units in cascade connection.



244 Page

## Appearance-oriented compact outdoor unit

### Split type Comfort series

For Comfort series, optimized flow temperature control is realized by DC inverter technology.

244 Page



### Monobloc type

Outdoor unit and hydraulic indoor unit can be installed anywhere due to compact size. Installation work can be performed easily only by connecting hydraulic pipes. DHW tank can be connected to indoor side.

246 Page




CORE TECHNOLOGY


High Efficiency

For Outdoor Unit  
Twin Rotary Compressor  
with Linear Control Injection Port

It realizes the high condensing temperature without overheating discharge gas temperature by Linear Control Injection process during compression. Therefore, the condensing temperature rises up higher than normal circuit. A higher hot water temperature is realized by controlling the injection amount according to the usage state.



Accurate temperature control  
by DC inverter technology




For Hydraulic Indoor Unit  
Class A pump

Energy saving pump with constant volume or pressure adjustment function.



Stainless steel buffer tank

Heat exchange amount is 25% higher than previous model. Energy saving performance is improved.



Easy Control



Hydraulic Indoor Unit Controller  
4 Heating mode

- 1. Automatic mode  
Comfort/Reduce mode switching automatically according to time program
- 2. Reduce mode  
Constant reduce temperature
- 3. Comfort mode  
Constant comfort temperature
- 4. Protection mode  
Stand-by mode with anti-frost protection

WATERSTAGE™ Lineup

Capacity (kW)	5	6	8	10	11	14	15	16	17
Split	NEW Super High Power series 3 phase Page 244  Hydraulic Indoor Unit/Outdoor Unit								
Split DHW integrated	High Power series Single phase Page 244  Hydraulic Indoor Unit/Outdoor Unit								
Monobloc	Compact series with hydraulic unit Page 246  Hydraulic Indoor Unit/Outdoor Unit								

\*: Tentative model name

EHPA Quality Label



Fujitsu General's WATERSTAGE\* have obtained the EHPA Quality Label\*\* by tests according to the international Standards EN14511 and EN17025. The EHPA Quality Label\*\* is a label that shows the end-consumer a quality heat pump unit on the market.  
\*: High Power split model  
\*\*: Check the validity of label at [www.ehpa.org/QL](http://www.ehpa.org/QL)

SG-Ready Label



SG-Ready is a defined standard by BWP\*\*\*, which makes it possible that the device can be integrated into a smart grid. Heat pumps, which are equipped with the SG-Ready Label, can receive signals from the power grid (and e.g. also from PV systems) about the available (unused renewable) energy (from wind, sun & water). Fujitsu General provides the SG-Ready compatibility to all new Heat Pumps series.  
\*\*\*BWP: the Federal German Heat Pump Association



## Split Type

Super high power series  
High power series  
Comfort series

**WATERSTAGE™**



### Super high power series

Hydraulic indoor unit:  
[3phase] WSYK170xxx\*  
Outdoor unit:  
[3phase] WOYK150LJL/WOYK170LJL

\*: Tentative model name



Hydraulic indoor unit  
3 Phase  
Outdoor unit  
3 Phase  
15/17 kW

### High power series

Hydraulic indoor unit:  
WSYG140DG6/[3phase] WSYK160DG9  
Outdoor unit:  
WOYG112LHT/WOYG140LCTA  
[3phase] WOYK112LCTA/WOYK140LCTA/  
WOYK160LCTA



Hydraulic indoor unit  
Single Phase/  
3 Phase  
Outdoor unit  
Single Phase  
11/14 kW  
3 Phase  
11/14/16 kW

### Comfort series

Hydraulic indoor unit:  
WSYA050DG6/WSYA100DG6  
Outdoor unit:  
WOYA060LFCA/WOYA080LFCA/  
WOYA100LFTA



Hydraulic indoor unit  
Outdoor unit  
5/6/8 kW  
10 kW

## Split DHW Integrated Type

High power series  
Comfort series

**WATERSTAGE™**



### High power series

Hydraulic indoor unit:  
WGYG140DG6/[3phase] WGYK160DG9  
Outdoor unit:  
WOYG112LHT/WOYG140LCTA  
[3phase] WOYK112LCTA/WOYK140LCTA/WOYK160LCTA



Hydraulic indoor unit  
Single Phase/  
3 Phase  
Outdoor unit  
Single Phase  
11/14 kW  
3 Phase  
11/14/16 kW

### Comfort series

Hydraulic indoor unit:  
WGYA050DG6/WGYA100DG6  
Outdoor unit:  
WOYA060LFCA/WOYA080LFCA/WOYA100LFTA



Hydraulic indoor unit  
Outdoor unit  
5/6/8 kW  
10 kW

## High leaving water temperature

### Super High power series:


High leaving water temperature of 60°C is kept even when outdoor temperature is down to -20°C without using backup heaters. Maximum leaving water temperature is 55°C without backup heater. Hot water supply temperature can be maintained even at -22°C outdoor temperature.



Super high power series

### High power series:

High leaving water temperature of 60°C is kept even when outdoor temperature is down to -20°C without using backup heaters.



High power series

### Comfort series:

Maximum leaving water temperature is 55°C without backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.



Comfort series

\* If you want to raise the hot water supply temperature, backup heaters can be used for auxiliary operation.


## High COP

Air to water heat pumps work with much more efficiency and save more energy than a traditional heating system.

Energy efficiency class

**A++**

### Seasonal space heating energy efficiency ( $\eta_s$ )




Condition : Outdoor Temp. 7°C Heating Temp. 35°C.

## 2 Zone individual control\*


2 Zone individual control (2 under floor heating zones or under floor heating + radiator zone, etc.)\*

\*: Optional parts are required.



## Automatic heating curve control

Automatic temperature regulation in accordance with heating curve (Depends on heating terminal and outdoor temperature)



# Monobloc Type

Comfort series

**Compact series**

Hydraulic indoor unit:

WSYP100DG6

Outdoor unit :

WPYA050LG / WPYA080LG / WPYA100LG




Hydraulic indoor unit

Outdoor unit 5 kW

8/10 kW

## High leaving water temperature


High leaving water temperature of 55°C keeps to -20°C outdoor temperature without additional heater.




## High COP

High COP is realized by using a DC twin rotary compressor, inverter technology, and high efficient water heat exchanger.

Energy efficiency class



## Compact & light weight design



## Features of the hydraulic indoor unit

- The compact Indoor unit provides two electrical back up heater, each with 3 kW capacity
- 12 L expansion vessel included
- No waste of space. DHW Kit installation inside the hydraulic unit possible.
- New generation controller. Connection by MODBUS protocol possible.
- Integrated heat metering (flow sensor included).




Hydraulic indoor unit

## Case Studies


### Split Type

2 emitter simultaneous heating (Individual control)

Floor heating + Radiator




Boiler connected to heating (Boiler + Heating)



### Split DHW Integrated Type


Single heating & Domestic Hot Water

Radiator + Domestic Hot Water



2 emitter simultaneous heating (Individual control) & Domestic Hot Water


Radiator + Domestic Hot Water




### Split Cascade System

2 emitter simultaneous heating (Individual control)

Floor heating + Radiator




Boiler connected to heating (Boiler + Heating)



### Monobloc Type


Single heating system

Floor heating



































Boiler connected to heating (Boiler + Heating)

Floor heating



Optional Parts

Product Name		Model Name	Split												Split DHW integrated type												Monobloc		
			Super High Power	High Power						Comfort						High Power						Comfort							
				3Ø		1Ø		3Ø		1Ø				1Ø		3Ø				1Ø				1Ø					
				15	17	11	14	11	14	16	5	6	8	10	11	14	11	14	16	5	6	8	10	5	8	10			
2nd Circuit Kit		UTW-KZSXE	●	●	●	●	●	●	●	●	●	●	—	—	—	—	—	—	—	—	—	—	—	—					
		UTW-KZDXE	—	—	—	—	—	—	—	—	—	—	●	●	●	●	●	●	●	●	—	—	—	—					
Boiler Connection Kit		UTW-KBSXD	●	●	●	●	●	●	●	●	●	●	—	—	—	—	—	—	—	—	—	—	—	—					
		UTW-KBDXD	—	—	—	—	—	—	—	—	—	—	●	●	●	●	●	●	●	●	—	—	—	—					
Balancing Vessel		UTW-TEVXA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
DHW Kit		UTW-KDWXG (Internal)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—					
		UTW-KDWXD (External)	●	●	●	●	●	●	●	●	●	●	__*1	__*1	__*1	__*1	__*1	__*1	__*1	__*1	●	●	●	●					
DHW Tank	200 Liter 300 Liter 400 Liter 	UTW-T20AXH UTW-T30AXH UTW-T40AXH	●	●	●	●	●	●	●	●	●	●	__*1	__*1	__*1	__*1	__*1	__*1	__*1	__*1	●	●	●	●					
	200 Liter 300 Liter 400 Liter 	UTW-T20BXH UTW-T30BXH UTW-T40BXH	●	●	●	●	●	●	●	●	●	●	__*1	__*1	__*1	__*1	__*1	__*1	__*1	__*1	●	●	●	●					
Circulating Pump		UTW-PHFYG	●	●	●	●	●	●	—	—	—	—	●	●	●	●	●	—	—	—	—	—	—	—					
Swimming Pool Kit		UTW-KSPXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
Heat Exchanger for Swimming Pool Kit		UTW-ESPXA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
Cooling Kit		UTW-KCLXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	__*2	__*2	__*2	—					
Regulation Extension Kit		UTW-KREXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●					
Low Noise Kit		UTW-KLNXE	●	●	●	●	●	●	—	—	—	—	●	●	●	●	—	—	—	—	—	—	—	—					
Drain Pan		UTW-KDPXA	—	—	—	—	—	—	●	●	●	—	—	—	—	—	—	●	●	●	—	—	—	—					
Cascade Master Kit (incl. LPB Clip)		UTW-KCMXE	●	●	●	●	●	—	—	—	●	—	—	—	—	—	—	—	—	—	—	—	—	—					
Cascade Slave Kit (incl. LPB Clip)		UTW-KCSXE	●	●	●	●	●	—	—	—	●	—	—	—	—	—	—	—	—	—	—	—	—	—					

Product Name	Model Name	Split												Split DHW integrated type												Monobloc		
		Super High Power		High Power						Comfort				High Power						Comfort						Compact		
		3Ø		1Ø		3Ø		1Ø				1Ø		3Ø		1Ø				1Ø								
		15	17	11	14	11	14	16	5	6	8	10	11	14	11	14	16	5	6	8	10	5	8	10				
HMI Kit		UTW-KHMXE*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
Remote Controller		UTW-C74TXF*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
		UTW-C74HXF*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
		UTW-C78XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
		UTW-C78XD-E*4	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
Room Thermostat		UTW-C55XA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
		UTW-C58XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
Outdoor Sensor Transmitter		UTW-MOSXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
RF Modules	 for BSB-Port	UTW-MRCXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
Web Server		UTW-KW1XD UTW-KW4XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
LPB Clip		UTW-KL1XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
MODBUS Clip		UTW-KMBXE	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7				
Base Heater		UTW-HAMXE	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—				
		UTW-HAMXF	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—				
Service Tool (incl. OCI700 Adaptor)		UTW-KSTXD	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5				
Service Tool Software		UTW-KPSXD	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6				
External Connect Kit		UTY-XWZXZ2	●	●	●	●	●	●	—	—	—	—	●	●	●	●	—	—	—	—	—	—	—	—				

\*1: DHW operation is possible without DHW Kit and DHW Tank.      ● : Available    — : Not Available  
\*2: Cooling operation is possible without cooling kit  
\*3: 19 Languages included, no separate Eastern European RC necessary. C74TXF: Built in Room Temperature sensor C74HXF: Built in Room temperature and Humidity sensor  
\*4: Eastern European Language(English, Czech Republic, Slovakia, Poland, Turkey, Hungary, Russia, Slovenia, Greece, Serbia)  
\*5: UTW-KL1XD is required for the connection.  
\*6: UTW-KW1XD or UTW-KW4XD is required for the connection.  
\*7: Additional optional part necessary




Installation Limitations

Equipment Installation


Split type Hydraulic indoor unit

- Hydraulic indoor unit is to be hang on the wall
- Weight < 65 kg (including water)
- Space for maintenance should be respected




Monobloc Type Hydraulic indoor unit

- Hydraulic indoor unit is to be hang on the wall
- Weight < 62 kg (including water)
- Distances for maintenance should be respected




Split DHW integrated type Hydraulic indoor unit

- Floor stand
- Weight 366 kg (including water)
- Space for maintenance should be respected.




Monobloc type Outdoor unit

- Floor stand
- Weight 72 kg (without water): WPYA080LG, WPYA100LG
- 49 kg (without water): WPYA050LG
- Distances for maintenance should be kept



Piping and Wiring

Split type



Series	Capacity range(kW)	H (m)	L (m)
Comfort	5	±20	5-30
	6		
	8		
	10		
High power	11	±15	5-20
	14		
	15	±15	5-30
	16		
	17	±15	5-30

\*For the outdoor unit installed below the indoor units: 25 m max. (15, 17 kW models)

Specifications & Dimensions

Split type Super high power series/High power series

Specifications

Model Name			Hydraulic indoor unit		WSYK170xxx*3		WSYK170xxx*3	
Capacity range			Outdoor unit		WOYK150LJL		WOYK170LJL	
7°C/35°C floor heating *1	Heating capacity		kW		15		17	
	Input power			15.00		17.00		
	COP			3.46		4.13		
	COP			4.33		4.12		
2°C/35°C floor heating *1	Heating capacity		kW		13.20		13.50	
	Input power			4.06		4.27		
	COP			3.25		3.16		
	COP			13.2		15.0		
-7°C/35°C floor heating*1	Heating capacity		kW		4.55		5.32	
	Input power			4.55		5.32		
	COP			2.90		2.82		
	COP			2.90		2.82		
Space heating characteristics*2								
Temperature application				°C	55	35	55	35
Energy efficiency class					A++	A++	A++	A++
Rated heat output(P <sub>rated</sub> )				kW	16	17	17	18
Seasonal space heating energy efficiency(η <sub>s</sub> )				%	130	164	130	161
Annual energy consumption				kWh	9913	8606	10225	9089
Sound power level		Hydraulic indoor unit		dB(A)	—		—	
		Outdoor unit			68		67	
					68	67	68	68
Hydraulic indoor unit Specification								
Power source				3 N 400 V 50 Hz				
Dimensions H×W×D				mm	—	—	—	—
Weight (Net)				kg	—	—	—	—
Water circulation		Min/Max	L/min	—	—	—	—	—
Buffer tank capacity				L	—	—	—	—
Expansion vessel capacity				L	—	—	—	—
Leaving water temperature range		Max	°C	—	—	—	—	—
Water pipe connection diameter		Flow/Return	mm	—	—	—	—	—
Backup heater		Capacity	kW	—	—	—	—	—
Outdoor unit specification								
Power source				3 N 400 V 50 Hz				
Current		Max	A	14.0		14.0		
Dimensions H × W × D				mm	1,428 × 1,080 ×480		1,428 × 1,080 ×480	
Weight (Net)				kg	138		138	
Refrigerant		Type (Global Warming Potential)			R410A (2,088)			
		Charge	kg	3.80		3.80		
Additional refrigerant charge amount				g/m	50		50	
Connection pipe	Diameter	Liquid	mm	Ø 9.52		Ø 9.52		
		Gas		Ø 15.88		Ø 15.88		
	Length	Min/Max	m	5/30		5/30		
	Length(Pre-charge)		m	15		15		
Height difference	Max	m	15		15			
	Heating	°C	-25 to 35		-25 to 35			


\*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.

\*2:All information of ErP can be available for downloaded from [www.fujitsu-general.com/global/products/erp-ecodesign/index.html](http://www.fujitsu-general.com/global/products/erp-ecodesign/index.html).


\*3:Tentative model name

Dimensions


Super high power series  
Outdoor Unit:  
WOYK150LJL/WOYK170LJL




High power series  
Outdoor Unit:  
WOYK112LHT/WOYK140LCTA



WOYK112LHT/WOYK140LCTA



Hydraulic Indoor Unit:  
WSYK170xxx\*3 (Super high power series)  
WSYG140DG6/WSYK160DG9 (High power series)



Specifications & Dimensions

Split type Comfort series

Specifications


Model Name			Hydraulic indoor unit		WSYA050DG6		WSYA100DG6		WSYA100DG6		WSYA100DG6	
			Outdoor unit		WOYA060LFCA		WOYA060LFCA		WOYA080LFCA		WOYA100LFCA	
Capacity range					5		6		8		10	
7°C/35°C floor heating * <sup>1</sup>	Heating capacity	kW	4.50		6.00		7.50		10.00			
	Input power		0.996		1.41		1.84		2.49			
	COP		4.52		4.27		4.08		4.02			
2°C/35°C floor heating * <sup>1</sup>	Heating capacity	kW	4.50		4.95		5.65		7.70			
	Input power		1.39		1.53		1.78		2.47			
	COP		3.24		3.24		3.17		3.12			
-7°C/35°C floor heating* <sup>1</sup>	Heating capacity	kW	4.10		4.60		5.70		7.40			
	Input power		1.47		1.74		2.23		2.97			
	COP		2.79		2.64		2.56		2.49			
Space heating characteristics** <sup>2</sup>												
Temperature application			°C		55		35		55		35	
Energy efficiency class					A+		A++		A+		A++	
Rated heat output(P <sub>rated</sub> )			kW		4		5		6		8	
Seasonal space heating energy efficiency(η <sub>s</sub> )			%		115		169		118		156	
Annual energy consumption			kWh		3026		2160		3886		5415	
Sound power level	Hydraulic indoor unit		dB(A)		46		46		46		46	
	Outdoor unit				65		63		65		69	
Hydraulic indoor unit Specification												
Power source			1 Ø 230 V 50 Hz									
Dimensions H×W×D			mm		800 × 450 × 457							
Weight (Net)			kg		42							
Water circulation			Min/Max		L/min		8.1/16.2		10.8/21.7		13.5/27.1	
Buffer tank capacity			L		16							
Expansion vessel capacity			L		8							
Leaving water temperature range			Max		°C 55							
Water pipe connection diameter			Flow/Return		mm Ø 25.4/Ø 25.4							
Backup heater			Capacity		kW 6.0(3.0kW×2pcs.)							
Outdoor unit specification												
Power source			1 Ø 230 V 50 Hz									
Current			Max		A		11.0		12.5		17.5	
Dimensions H × W × D			mm		620 × 790 ×290							
Weight (Net)			kg		41							
Refrigerant			Type (Global Warming Potential)		R410A (2,088)							
			Charge		kg		1.10		1.40		1.80	
Additional refrigerant charge amount					g/m		25		Ø 6.35		Ø 9.52	
Connection pipe	Diameter	Liquid	mm		Ø 12.7							
		Gas	mm		Ø 15.88							
	Length	Min/Max	m		5/30							
	Length(Pre-charge)		m		15							
Operation range	Height difference	Max	m		20							
		Heating	°C		-20 to 35							

\*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.


\*2:All information of ErP can be available for downloaded from [www.fujitsu-general.com/global/products/erp-ecodesign/index.html](http://www.fujitsu-general.com/global/products/erp-ecodesign/index.html).

Dimensions


Outdoor Unit:  
WOYA060LFCA/WOYA080LFCA



WOYA100LFCA



Hydraulic Indoor Unit:  
WSYA050DG6/WSYA100DG6



Split DHW Integrated type High power series

Specifications

Model Name			Hydraulic indoor unit		WGYG140DG6		WGYG140DG6		WGYK160DG9		WGYK160DG9		WGYK160DG9	
			Outdoor unit		WOYG112LHT		WOYG140LCTA		WOYK112LCTA		WOYK140LCTA		WOYK160LCTA	
Capacity range					11		14		11		14		16	
7°C/35°C floor heating *1	Heating capacity	kW	10.80		13.50		10.80		13.50		15.17			
	Input power		2.54		3.23		2.51		3.20		3.70			
	COP		4.25		4.18		4.30		4.22		4.10			
2°C/35°C floor heating *1	Heating capacity	kW	10.77		12.00		10.77		13.00		13.50			
	Input power		3.44		3.87		3.40		4.15		4.34			
	COP		3.13		3.10		3.17		3.13		3.11			
-7°C/35°C floor heating*1	Heating capacity	kW	10.38		11.54		10.38		12.20		13.50			
	Input power		4.32		5.08		4.28		5.13		5.40			
	COP		2.40		2.27		2.43		2.38		2.50			
Space heating characteristics**														
Temperature application			°C		55		35		55		35		55	
Energy efficiency class			A+		A++		A+		A+		A+		A+	
Rated heat output(P <sub>rated</sub> )			kW		9		11		11		13		14	
Seasonal space heating energy efficiency(η <sub>s</sub> )			%		112		151		113		148		117	
Annual energy consumption			kWh		6704		6062		8041		6824		6669	
Sound power level	Hydraulic indoor unit	dB(A)	46		46		46		46		46		46	
	Outdoor unit		68		69		69		68		70			
Domestic hot water characteristics**														
Load profile									L					
Energy efficiency class									A					
Energy efficiency(η <sub>wh</sub> )			%						88					
Annual electricity consumption			kWh						1166					
Hydraulic indoor unit Specification														
Power source					1 Ø 230 V 50 Hz				3 N 400 V 50 Hz					
Dimensions H×W×D			mm		1,840× 648 × 698									
Weight (Net)			kg		152									
Water circulation			L/min		19.5/39.0		24.4/28.7		19.5/39.0		24.4/48.7		27.4/54.8	
DHW capacity			L		190									
Hot water heater capacity			kW		1.5									
Expansion vessel capacity			L		12									
Leaving water temperature range			Max		°C				60					
Water pipe connection diameter			Flow/Return		mm		Ø 25.4/Ø 25.4							
Hot water pipe connection diameter			mm		Ø 19.05									
Backup heater			Capacity		kW		6.0(3.0kW×2pcs.)				9.0(3.0kW×3pcs.)			
Outdoor unit specification														
Power source					1 Ø 230 V 50 Hz				3 N 400 V 50 Hz					
Current			Max		A		22.0		25.0		8.5		10.5	
Dimensions H × W × D			mm		1,290 × 900 ×330									
Weight (Net)			kg		92				99					
Refrigerant			Type (Global Warming Potential)		R410A (2,088)									
Additional refrigerant charge amount			Charge		kg		2.50							
Connection pipe	Diameter	Liquid	mm		Ø 9.52									
		Gas	mm		Ø 15.88									
	Length	Min/Max	m		5/20									
		Length(Pre-charge)	m		15									
Operation range	Height difference	Max	m		15									
		Heating	°C		-25 to 35									



Specifications & Dimensions

Split DHW Integrated type Comfort series

Specifications: Split DHW Integrated type Comfort series


Model Name		Hydraulic indoor unit		WGYA050DG6		WGYA100DG6		WGYA100DG6		WGYA100DFTA	
		Outdoor unit		WOYA060LFCA		WOYA060LFCA		WOYA080LFCA		WOYA100LFTA	
Capacity range				5		6		8		10	
7°C/35°C floor heating *1	Heating capacity	kW	4.50		6.00		7.50		10.00		
	Input power		0.996		1.41		1.84		2.49		
	COP		4.52		4.27		4.08		4.02		
2°C/35°C floor heating *1	Heating capacity	kW	4.50		4.95		5.65		7.70		
	Input power		1.39		1.53		1.78		2.47		
	COP		3.24		3.24		3.17		3.12		
-7°C/35°C floor heating*1	Heating capacity	kW	4.10		4.60		5.70		7.40		
	Input power		1.47		1.74		2.23		2.97		
	COP		2.79		2.64		2.56		2.49		
Space heating characteristics*2											
Temperature application		°C	55	35	55	35	55	35	55	35	
Energy efficiency class			A+	A++	A+	A++	A+	A++	A+	A++	
Rated heat output(P <sub>rated</sub> )		kW	4	4	5	5	6	7	8	8	
Seasonal space heating energy efficiency(η <sub>s</sub> )		%	115	169	115	169	118	156	113	155	
Annual energy consumption		kWh	3026	2160	3180	2505	3886	3375	5415	4415	
Sound power level	Hydraulic indoor unit	dB(A)	46		46		46		46		
	Outdoor unit		65	60	65	63	65	69	68	69	
Domestic hot water characteristics*2											
Load profile			L								
Energy efficiency class			A+								
Energy efficiency(η <sub>wh</sub> )		%	120								
Annual electricity consumption		kWh	880								
Hydraulic indoor unit Specification											
Power source			1 Ø 230 V 50 Hz								
Dimensions H×W×D		mm	1,840× 648 × 698								
Weight (Net)		kg	152								
Water circulation		L/min	8.1/16.2		10.8/21.7		13.5/27.1		18.1/36.1		
DHW capacity		L	190								
Hot water heater capacity		kW	1.5								
Expansion vessel capacity		L	12								
Leaving water temperature range		Max °C	55								
Water pipe connection diameter		Flow/Return mm	Ø 25.4/Ø 25.4								
Hot water pipe connection diameter		mm	Ø 19.05								
Backup heater		Capacity kW	6.0(3.0kW×2pcs.)								
Outdoor unit specification											
Power source			1 Ø 230 V 50 Hz								
Current		Max A	11.0		12.5		17.5		18.5		
Dimensions H × W × D		mm	620 × 790		×290		42		830 × 900 ×330		
Weight (Net)		kg	41				60		60		
Refrigerant		Type (Global Warming Potential)	R410A (2,088)								
Charge		kg	1.10		1.40		1.80		1.80		
Additional refrigerant charge amount		g/m	25		40		9.52		9.52		
Connection pipe	Diameter	Liquid mm	Ø 12.70		Ø 6.35		Ø 15.88		Ø 9.52		
		Gas mm									
	Length	Min/Max m	5/30		15		20				
		Length(Pre-charge)	m								
Operation range	Height difference	Max m									
	Heating °C		-20 to 35								

\*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.


\*2:All information of ErP can be available for downloaded from [www.fujitsu-general.com/global/products/erp-ecodesign/index.html](http://www.fujitsu-general.com/global/products/erp-ecodesign/index.html).

Dimensions


Outdoor Unit:  
WOYA060LFCA/WOYA080LFCA



WOYA100LFTA



Hydraulic Indoor Unit:  
WGYA050DG6/WGYA100DG6



Monobloc type

Specifications

Model Name		Hydraulic indoor unit		WSYP100DG6						
Capacity range		Outdoor unit		WPYA050LG		WPYA080LG		WPYA100LG		
				5		8		10		
7°C/35°C floor heating *1	Heating capacity	kW	5.00		8.00		10.00			
	Input power		1.19		1.78		2.30			
	COP		4.20		4.50		4.35			
2°C/35°C floor heating *1	Heating capacity	kW	3.65		4.35		4.90			
	Input power		1.07		1.23		1.44			
	COP		3.40		3.55		3.40			
-7°C/35°C floor heating*1	Heating capacity	kW	3.55		7.10		8.00			
	Input power		1.38		2.93		3.32			
	COP		2.57		2.42		2.41			
Space heating characteristics**2										
Temperature application		°C	55	35	55	35	55	35		
Energy efficiency class			A+	A++	A+	A++	A+	A++		
Rated heat output (P <sub>rated</sub> )		kW	4	4	6	7	7	8		
Seasonal space heating energy efficiency(η <sub>s</sub> )		%	118	171	123	168	118	167		
Annual energy consumption		kWh	3055	1952	3828	3580	4491	3700		
Sound power level		Outdoor unit	dB (A)	62	61	65	68			
Hydraulic indoor unit Specification										
Power source			1 Ø 230 V 50 Hz							
Dimensions H×W×D		mm	803 × 450 × 457							
Weight (Net)		kg	40							
Buffer tank capacity		L	22							
Expansion vessel capacity		L	12							
Water pipe connection diameter		Flow/Return	mm	Ø 25.4/Ø 25.4						
Backup heater		Capacity	kW	6.0(3.0kW×2pcs.)						
Outdoor unit specification										
Power source			1 Ø 230 V 50 Hz							
Dimensions H × W × D		mm	675 × 825 × 300		882 × 850 × 330		882 × 850 × 330			
Weight (Net)		kg	49		72		72			
Current		Max	A		15.2		17.5			
Water circulation		Min/Max	L/min		5.0/20.0		10.0/30.0			
Water pipe connection diameter		Flow/Return	mm		Ø 19.05/Ø 19.05		Ø 25.4/Ø 25.4			
Refrigerant		Type (Global Warming Potential)	R410A (2,088)							
Charge		kg	1.05		1.72					
Leaving water temperature range		Max	°C		55					
Operation range		Heating	°C		-20 to 35					