

**High Static Pressure Duct (48,000 BTU) Indoor Unit
For Heat-pump Airstage VRF System**

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

FEATURES

- Quiet 3-speed fan
- Adjustable Static pressure from 0.4 to 0.8 in.WG
- Very low power usage
- Dual direction drain piping
- 10 year Extended Warranty on parts and compressor. See Warranty Statement.


STATIC PRESSURE

Static Pressure Range - in.WG [Pa] 0.40 to 1.00 [100 to 250]
 Standard Static Pressure - in.WG [Pa] 0.40 [100]

CAPACITY

Capacity - Cooling - Btu/h [kW] 48,000 [14.1]
 Capacity - Heating - Btu/h [kW] 54,000 [15.8]

PIPING ACCESSORIES

UTP-AX090A Separation Tube - 2-Pipe - 90 MBH or Less
 UTP-AX180A Separation Tube - 2-Pipe - 91 to 180 MBH
 UTP-AX567A Separation Tube - 2-Pipe - 180 MBH or More

ELECTRICAL

Power Source 208 / 230V, 1-Phase, 60Hz
 Available Voltage Range - VAC 187 to 253
 Input Power - W 750

CONTROLLER

UTY-RNKU Wired Remote Control
 UTY-RHKU Simple Remote (WITHOUT Master Control) (1/16 units)
 UTY-LNHU Wireless Remote Controller (requires IR Receiver)

Max Circuit Breaker - A 20
 Minimum Circuit Ampacity - MCA - A 3.93
 Fuse - A (V) 3.15 (250) + Fan 10 (250)

UTY-DCGY Central Remote Controller (100 units)
 UTY-DTGYZ1 Touch Panel Controller with Internet (400 units)

FAN

Fan Type 2X (Sirocco)
 Airflow Rate - High - CFM [m³/h] 1,766 [3,000]
 Airflow Rate - Medium - CFM [m³/h] 1,589 [2,700]
 Airflow Rate - Low - CFM [m³/h] 1,354 [2,300]

ACCESSORIES

#N/A #N/A
 UTD-LF60KA Long Life Filter
 UTY-TEKX External Switch Controller. Use with 3-Wire remotes only.
 UTY-XSZX Remote Sensor for ducted units

SOUND PRESSURE

Sound Pressure Level - dB(A) 40/43/47

WIRING

Communication Cable LonWorks (Fujitsu Pink Cable. See AE Bulletin 009)

WEIGHT AND DIMENSIONS

Enclosure - Net Weight - lbs [kg] 100 [45]
 Enclosure - Gross Weight - lbs [kg] 111 [50]
 Dimensions - Net (H x W x D) - in [mm] 15-3/4 x 41-5/16 x 19-11/16 [400 x 1,050 x 500]
 Dimensions - Gross (H x W x D) - in [mm] 18-1/8 x 48-7/16 x 25-3/16 [460 x 1,230 x 640]

PIPING

Connection Pipe Diameter - Liquid (Flare) - in [mm] ø 3/8 [9.52]
 Connection Pipe Diameter - Gas (Flare) - in [mm] ø 3/4 [19.05]
 Connection Pipe Diameter - Drain (ID; OD) - in [mm] ø 3/4 [19.05]
 Drain-Pump Optional

ETL

E.T.L. 91987

TEMPERATURE SETTINGS

Operating Temp. Cooling (DB) - °F [°C] 64 to 90 [18 to 32]
 Operating Temp. Heating (DB) - °F [°C] 50 to 86 [10 to 30]

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).




Fujitsu General America, Inc.
 353 Route 46 West
 Fairfield, NJ 07004
 Toll Free: (888) 888-3424
 Fax: (973) 836-0453
 www.airstagevrf.com

High Static Pressure Duct (48,000 BTU) Indoor Unit
For Heat-pump Airstage VRF System

DIMENSIONS

Unit: In. (mm)



Fujitsu General America, Inc.
353 Route 46 West
Fairfield, NJ 07004
Toll Free: (888) 888-3424
Fax: (973) 836-0453
www.airstagevrf.com