

CASED/UNCASED COILS FOR GAS AND OIL FURNACES



FCC Series

R-410A

Airflow capacities 450-1,700 CFM and
600-1,900 CFM

Up to 18 SEER AC, HP, and Furnace
applications



BENEFITS AT-A-GLANCE

EVAPORATOR COIL:
All Aluminum

WARRANTY²:
Conditional parts – 10 years

- Fujitsu Indoor Coils are designed for use with Fujitsu outdoor units and are available for vertical upflow or downflow, and horizontal left or horizontal right airflow. When matched with Fujitsu outdoor units, the coils provide a nominal capacity range from 18,000 BTU/HR [5.24 kW] to 48,000 BTU/HR [14.06 kW].
- Constructed of aluminum fins bonded to internally grooved copper tubing.
- Coils are tested at the factory with an extensive refrigerant leak check.
- Coils have sweat refrigerant connections.
- Ideally suited for new installations or add on air conditioning.
- Feature two sets of 3/4" [14.1 mm] N.P.T. Condensate drain connections for ease of connection.
- Coils are AHRI certified for system application with variety of Fujitsu outdoor units.
- Condensate drain pan is constructed of high grade, heat resistant, corrosion free thermal-set material.
- Compatible with Germicidal Light System (UV resistant)
- Bi-Directional airflow eliminates the need to switch any internal components from horizontal left to right.
- Unique drain pan design maximizes application flexibility and condensate removal.
- Universal Duct Flanges are included with all coil models.

²For complete details of the limited warranties, including applicable terms and conditions, contact your local contractor or go to www.fujitsugeneral.com for a copy of the product warranty certificate.

FUJITSU GENERAL AMERICA, INC.
340 Changebridge Road
Pine Brook, NJ 07058
Toll Free: (888) 888-3424
Local: (973) 575-0380
www.fujitsugeneral.com

A subsidiary of
Fujitsu General Limited

